

Product Data Sheet

SHL1200 Shearlock

The SHL-1200 shearlocks are part of our family of electronic locking devices. These units are ideal for traditional single action doors (one way opening), or for double action doors (swing-through) providing the door closers are of a good standard.

They provide discreet high security locking with the minimum of fuss. The shearlocks have a holding force up to 1200kg, and include lock status monitoring as standard. Additionally, they will accept free voltage of 12 to 48vdc.

A full range of accessories are available to enable the shearlocks to be fitted to most doors, even glass.



Specification

Voltage: 12 - 48vdc
Finish: Stainless Steel, Coated
Working Current: 630mA @ 12Vdc, 315mA @ 24Vdc
In-Rush Current: 2.1A @ 12Vdc , 1.05A @ 24Vdc
Dimensions: 268 x 30 x 35mm (l x w x d)

Model #

NRAWSHL-1200
NRAWSHL-1200-H
NRAWSHL-1200-GH

Description

Shearlock, monitored, up to 1200Kg, 12-48vdc
Surface housing for NRAWSHL-1200 (pair)
Glass door Surface housing for NRAWSHL-1200 (pair)

Nigel Rose (Marketing Services) Ltd

'The Dedicated Locksmiths Wholesaler'

Unit 4 Lincoln Park, Lincoln Road, Cressex Business Park, High Wycombe, Bucks HP12 3ES

Telephone: 01494 438 118 Fax: 01494 532 400

www.nigelrosems.co.uk e-mail: info@nigelrosems.co.uk